


# 1110

## Phase-Converting AC Drive



# 1110

Phase-  
Converting  
AC Drive

### Overview

The 1110 provides reliable, efficient, cost-effective variable-frequency (V/Hz) or flux vector control of ordinary three-phase AC motors from a single-phase power source. It incorporates the latest technologies in insulated gate bipolar transistors (IGBTs), pulse-width modulation (PWM), and digital signal processing (DSP) to deliver optimum motor performance, complete programmability, and simplicity of operation.

### Performance Flexibility

The 1110 accommodates a broad range of performance requirements. Units may be configured for constant-torque operation for heavy-duty cyclic loads, variable-torque operation for medium-duty requirements, or extended-torque operation for centrifugal loads such as fans and pumps. The drive operates in a transducerless vector control mode that does not require a feedback device and produces full torque to base speed with full starting torque. For demanding applications, an incremental encoder or resolver interface can be added for precise position, velocity, and torque regulation and improved dynamic performance. Dual- and triple-encoder interfaces are also available for position-following or dual-transducer applications. Variable-frequency control is alternately available for applications that do not require critical velocity or torque control. Several controller options are available to meet differing application requirements.

### Motor-Independent Design

The 1110 can operate any standard- or inverter-duty AC induction or synchronous motor, making it ideal for retrofits and new applications alike. A unique, proprietary digital current regulator (DCR) tunes the drive continuously in real time, eliminating the usual current-loop tuning process required by conventional drives. Digital space vector (DSV) control can be selected for reduced motor noise and low current ripple.

### Auto Tuning

Once routine electrical connections have been made, simple-to-use auto-tuning features adjust virtually all motor- and load-dependent parameters. No motor maps are required. Simply enter basic motor information from the nameplate, and the advanced setup routines do the rest. The drive is completely tuned within minutes.

### Application Software

A wide variety of software options is available to tailor the 1110 to an application, from a fully featured velocity/torque control for general purposes to a host of powerful programs pre-engineered for specific applications. Customization is possible with many programs using UEdit™, a Windows-based programming tool that lets users extend an application using IEC 1131 standard ladder diagrams and function blocks.

### Digital Setup, Easy Operation

A keypad and liquid crystal display provide a simple interface for setting and viewing operating parameters and diagnostics. All controller settings are made digitally for precision and repeatability. Readouts and fault messages are displayed in readily understandable language. An optional graphic display provides a variety of visual formats for accessing drive information.

**Overview***(continued)***Multiaxis Operation**

A built-in high-speed synchronous communication port allows the motion of multiple slave drives to be precisely coordinated. With optional master/slave software, the velocity ratio and position phasing of the drives can also be controlled. Multiple motors can be operated in parallel from a single drive using variable-frequency control.

**Power Quality**

A built-in link choke provides near-unity overall power factor and low harmonic line currents at all motor speeds.

**Protection and Advanced Diagnostics**

The 1110 monitors its operating conditions and provides a comprehensive set of overload, short circuit, and other electronic protective features to ensure safe, reliable operation. Faults indications are displayed in plain language. A log maintains a history of fault occurrences and externally triggered events.

**Serial Connectivity**

A fully isolated RS-422/485 serial interface is provided for connecting the drive to a process controller, communication network, or programmable controller. A variety of popular communication protocols is available. The 100 MHz module also accepts an AnyBus module with numerous industry-standard protocol options and a MaxStream module for wireless communications. An RS-232 connection is also provided on 40 and 100 MHz controllers for connecting a personal computer. Windows-based PCs can set up, monitor, and control a network of drives using optional DriveLink™ or UEdit™ software. Drive Archive™ and Drive Chart™ for the Palm OS make it easy to save and restore setups and capture charts using a handheld computer.

**Packaging**

Compact and rugged, the 1110 is available either enclosed or as an open chassis for mounting inside an enclosure. Both versions can be foot-mounted to a wall or subplate or flange-mounted through a cutout to dissipate heat outside an enclosure.

**Features & Benefits****General**

- 24-bit digital signal processor (DSP) for fast, dynamic response
- 128 kilobytes battery backup memory for application setup data
- 1.5 megabytes scratch pad memory and 3.0 megabytes firmware memory
- Clock/calendar maintains accurate time during power outage
- Sine-coded PWM waveform output for improved torque performance
- High-switching-frequency IGBT devices for smooth, quiet operation
- Digital current regulator for high-speed operation and fast response
- Digital space vector control for reduced motor noise and low current ripple
- Flux vector control for full starting torque and full torque to base speed
- Variable-frequency operation for simple control of motor speed
- Internal control loop for maintaining speed with sudden load changes
- Automatic field weakening for speeds up to three times base speed
- Integral DC link choke for high power factor and low total harmonic distortion
- Optional dynamic braking for fast deceleration or energy absorption
- Power disturbance ride-through for reducing nuisance trips
- User-programmable analog and digital inputs and outputs
- Through-hole heat sink mounting of chassis units for dissipating heat externally
- Optional NEMA 1 (IP23) and NEMA 4 (IP66) enclosures

**Ease of Installation, Setup, and Maintenance**

- Automated setup features require no chart recorders or meters
- Software calibration and adjustment eliminates tuning components
- Digital parameter adjustment for precise and repeatable settings
- Software input and output scaling eliminates potentiometers
- Complete, self-contained package requires minimal option boards
- Identical control boards across full power range reduces spare parts

**Ease of Use**

- Touch keypad for easy parameter adjustment and access to displays
- Two line descriptive plain-language display with numerical and bar graph readouts
- Comprehensive fault diagnostics displayed in plain language
- Real-time motion information and time-stamped fault log

**Safe, Reliable Operation**

- Extensive electronic protection circuits
- Tolerant of AC line voltage and frequency fluctuations
- S-curve acceleration reduces shock and extends equipment life
- Multilevel security code prevents unauthorized parameter changes
- Lockout of local operator controls for safe remote operation

## Specifications **Electrical**

### Input Supply

Voltage:	220 to 240 or 440 to 480 V AC, single-phase Phase sequence insensitive
Voltage tolerance:	-10% of minimum, +10% of maximum
Frequency:	47 to 63 Hz
Power factor:	Displacement: 0.89 at all loads and speeds Overall: 0.75 at rated load

### Output Rating

Voltage:	Zero to 90% of input supply voltage, three-phase
Frequency:	Zero to 120 Hz for transducerless vector control Zero to 180 Hz for transducer-based vector control Zero to 300 Hz for variable-frequency control
Switching frequency:	16 MHz control: 1, 2, 4, 8, and 16 kHz 20, 40, and 100 MHz controls: 1 to 12 kHz, programmable

### Service Conditions

Efficiency:	97% nominal at rated switching frequency									
Overload current:	<table><thead><tr><th><i>Torque</i></th><th><i>Overload (1 min)</i></th><th><i>Maximum</i></th></tr></thead><tbody><tr><td>Constant</td><td>150% to 200% of rated</td><td>200% of rated</td></tr><tr><td>Variable</td><td>120% to 150% of rated</td><td>140% to 160% of rated</td></tr></tbody></table>	<i>Torque</i>	<i>Overload (1 min)</i>	<i>Maximum</i>	Constant	150% to 200% of rated	200% of rated	Variable	120% to 150% of rated	140% to 160% of rated
<i>Torque</i>	<i>Overload (1 min)</i>	<i>Maximum</i>								
Constant	150% to 200% of rated	200% of rated								
Variable	120% to 150% of rated	140% to 160% of rated								

## Environmental

Operating temperature:	Control section: 32° to 131° F (0° to 55° C) Heat sink (standard): 32° to 104° F (0° to 40° C) Heat sink (derated): 32° to 122° F (0° to 50° C)
Storage temperature:	-40° to 158° F (-40° to 70° C)
Operating humidity:	95% maximum, noncondensing
Altitude:	To 3,300 ft (1,000 m) without derating

## Performance

### Frequency Control (16 MHz control)

Range:	Zero to base speed at full torque Base speed to 300 Hz at constant power
Resolution:	0.024% with analog input (12-bit) 0.1 Hz with digital input

### Velocity Control (20, 40, and 100 MHz controls)

Range:	Zero to base speed at full torque Base speed to 180 Hz at constant power with transducer Base speed to 120 Hz at constant power without transducer
Regulation:	±0.001% of base speed, down to zero, with transducer ±0.5% of base speed, 2 Hz and above, without transducer

### Torque Control (20, 40, and 100 MHz controls)

Starting torque:	Constant torque: zero to 150% of rated Variable torque: zero to 120% of rated
Regulation:	±3.0% of maximum with transducer ±10% of maximum without transducer

## Inputs and Outputs

### Analog Inputs

16 and 20 MHz controls: Three (3) 12-bit analog inputs (0 to +10 V DC, ±10 V DC, and 0 to 20 mA)

40 and 100 MHz controls: Three (3) 12-bit analog inputs (±10 V DC or 0 to 20 mA)

Analog Interface Module: Additional eight (8) 12-bit analog inputs (0 to +10 V DC or 0 to 20 mA)

### Analog Outputs

16 and 20 MHz controls: Two (2) 12-bit analog outputs (±10 V DC)

40 and 100 MHz controls: Two (2) 12-bit analog outputs (±10 V DC and 0 to 20 mA)

Analog Interface Module: Additional four (4) 12-bit analog outputs (±10 V DC)

### Digital Inputs

20 MHz control: Eleven (11) digital inputs (require sink of 1 mA to common)

16, 40, and 100 MHz controls: Twelve (12) digital inputs (require sink of 1 mA to common)

Converter Interface Module: Provision for input converters rated 2.5 to 28 V DC @ 30 mA,  
90 to 140 V AC @ 11 mA, and 180 to 280 V AC @ 5 mA

### Digital Outputs

16 and 20 MHz controls, 40 and 100 MHz mixed I/O controls: Three (3) digital outputs (Form C contacts rated 250 V AC @ 5 A, Form A contact rated 250 V AC @ 5 A, and open-collector driver rated 24 V DC @ 500 mA)

40 MHz contact I/O control: Three (3) Form A contacts rated 250 V AC @ 5 A

40 and 100 MHz logic I/O controls: Six (6) digital outputs (open-collector drivers rated 24 V DC @ 500 mA)

Converter Interface Module: Provision for output converters rated 5 to 60 V DC @ 3 A,  
12 to 140 V AC @ 3 A, or 24 to 280 V AC @ 3 A; or for normally open or normally closed relay converters rated 250 V AC @ 8 A

**Specifications***(continued)***Serial Communications****Asynchronous**

Port(s):

16 and 20 MHz controls: RS-422/485, isolated  
40 MHz control: RS-232/422/485, isolated,  
and RS-422/485100 MHz control: RS-232/422/485, isolated,  
and (2) RS-422/485

Protocols:

ANSI-x3.28-2.5-A4, standard; Allen-Bradley DF1,  
Modicon RTU, and Johnson Controls N2  
protocols available**Synchronous**

Port:

20, 40, and 100 MHz controls:  
RS-485 for high-speed master/slave networking**Communication Modules**

Provisions:

100 MHz control: one AnyBus and one MaxStream module

AnyBus options:

ControlNet, DeviceNet, Ethernet, Interbus,  
LonWorks, Modbus Plus, Profibus DPV1

MaxStream options:

900 MHz and 2.4 GHz wireless communication modules

**Protection**

The following hardware conditions are detected. Additional protective features are provided by the application software.

- Ground fault
- Motor phase-to-phase short circuit
- DC bus overvoltage
- DC bus undervoltage
- Instantaneous overcurrent
- Motor overload
- Heat sink overtemperature
- Ambient overtemperature
- Power transistor fault
- Logic power undervoltage
- Memory malfunction
- Processor not running fault

**Options****Transducers**

A motor-mounted incremental encoder or resolver and corresponding interface may be used for highest performance. The resolver interface provides an encoder emulation for paralleling feedback to other devices. Dual- and triple-encoder options are also available for position-following or dual-transducer applications.

**Expanded Analog I/O**

An analog interface module may be used instead of a feedback interface to expand the analog I/O capabilities of the drive. The module provides eight additional inputs and four additional outputs.

**Dynamic Braking**

The dynamic braking option is factory installed in the drive. Appropriately sized external braking resistors are required.

**Packaged Drives**

Drives may be ordered as part of a packaged system including a circuit breaker, operator devices, and additional system components mounted inside a NEMA 4 (IP66) enclosure.

**Power Range**

Input Voltage	Constant-Torque Applications	Variable-Torque Applications
230 V AC	1 1/2-40 hp (1.1-30 kW)	2-50 hp (1.5-37 kW)
460 V AC	1 1/2-75 hp (1.1-56 kW)	2-100 hp (1.5-75 kW)

Consult factory for other powers. Other voltages require appropriate derating or adjustment of the switching frequency.

**UNICO—Worldwide**

All trade designations are provided without reference to the rights of their respective owners.

Specifications subject to change without notice.

1110.20 2/05

**Corporate Headquarters**

UNICO, Inc.  
3725 Nicholson Road  
P. O. Box 0505  
Franksville, Wisconsin  
53126-0505  
USA

voice: 262.886.5678  
fax: 262.504.7396

www.unicous.com

**United States**

Novi, Michigan  
248.380.7610

New Lenox, Illinois  
815.485.5775

Sandy, Utah  
801.501.7586

**Canada**

Mississauga,  
Ontario  
905.602.4677

**South America**

El Tigre, Venezuela  
58.283.241.4024

**Europe**  
Milton Keynes,  
England  
44.1908.260000

Wilnsdorf, Germany  
49.2739.303.0

**Asia**

Osaka, Japan  
81.66.945.0077

Beijing, China  
86.10.6218.6365